

TUERCAS HEXAGONALES GRADO 8

ASME B 18.2.2 - grado 8 - Templadas y revenidas



Paso grueso - UNC / USS

Grado 8

Medida	Dimensiones		Precio x 100 unidades
	Entrecara (S)	Altura (M)	
1/4 - 20	11,11	5,55	825
5/16 - 18	12,70	6,75	1.050
3/8 - 16	14,29	8,30	1.350
7/16 - 14	17,46	9,52	2.400
1/2 - 13	19,05	11,11	2.850
9/16 - 12	22,22	12,30	5.970
5/8 - 11	23,81	13,89	4.800
3/4 - 10	28,57	16,30	7.650
7/8 - 9	33,33	19,05	11.550
1" - 8	38,10	21,83	18.750
1 1/8 - 7	42,86	24,60	41.400
1 1/4 - 7	47,62	27,00	55.050
1 1/2 - 6	57,15	32,54	105.975

Paso fino - UNF / SAE

Grado 8

Medida	Dimensiones		Precio x 100 unidades
	Entrecara (S)	Altura (M)	
1/4 - 28	11,11	5,55	945
5/16 - 24	12,70	6,75	1.320
3/8 - 24	14,29	8,30	1.710
7/16 - 20	17,46	9,52	3.075
1/2 - 20	19,05	11,11	3.570
9/16 - 18	22,22	12,30	6.675
5/8 - 18	23,81	13,90	6.000
3/4 - 16	28,57	16,30	9.600
7/8 - 14	33,33	19,05	16.950
1" - 14	38,10	21,83	26.250
1 1/4 - 12	47,62	27,00	61.650
1 1/2 - 12	57,15	32,54	116.250

Precios en pesos sin IVA.

08

01/09/19

fastener S.R.L.